



**brennenstuhl®**

# SICHERHEITSINFORMATIONEN

## SAFETY INFORMATION

---

|           |                                     |           |                              |           |                              |
|-----------|-------------------------------------|-----------|------------------------------|-----------|------------------------------|
| <b>DE</b> | Sicherheitsinformationen            | <b>HU</b> | Biztonsági információk       | <b>LT</b> | Saugos informacija           |
| <b>EN</b> | Safety information                  | <b>RU</b> | Информация о безопасности    | <b>LV</b> | Drošības informācija         |
| <b>FR</b> | Informations sur la sécurité        | <b>TR</b> | Güvenlik bilgileri           | <b>HR</b> | Sigurnosne informacije       |
| <b>NL</b> | Veiligheidsinformatie               | <b>FI</b> | Turvallisuustiedot           | <b>RO</b> | Informații privind siguranța |
| <b>IT</b> | Informazioni sulla sicurezza        | <b>GR</b> | Πληροφορίες για την ασφάλεια | <b>BG</b> | Информация за безопасност    |
| <b>SE</b> | Säkerhetsinformation                | <b>PT</b> | Informações de segurança     | <b>DK</b> | Oplysninger om sikkerhed     |
| <b>ES</b> | Información de seguridad            | <b>EE</b> | Ohutusalane teave            | <b>NO</b> | Sikkerhetsinformasjon        |
| <b>PL</b> | Informacje dotyczące bezpieczeństwa | <b>SK</b> | Bezpečnostné informácie      | <b>UA</b> | Інформація з техніки безпеки |
| <b>CZ</b> | Bezpečnostní informace              | <b>SI</b> | Varnostne informacije        | <b>AR</b> | معلومات السلامة              |

---

[WWW.BRENNENSTUHL.COM](http://WWW.BRENNENSTUHL.COM)

04/11/2024



**CE EAC**

**Art. 1 159780 615**

**Hugo Brennenstuhl GmbH & Co. KG,  
Seestr.1-3, D-72074 Tübingen**

lectra technik ag, Blegistrasse 13, CH-6340 Baar  
[service@brennenstuhl.com](mailto:service@brennenstuhl.com)

4



007123

667659

4121 4623

0483917/4323



SDL PD 05 DE 4121 Art. 1 159780 615  
1,5 m H05VV-F 3G1,5 0483916/2820  
3680W MAX, 16A 230V~

USB type A port: 5,0V=2,4A MAX 12,0W, 9,0V=2,0A MAX 18,0W;  
12,0V=1,5A MAX 18,0W

USB-PD: 5,0V=3,0A MAX 15,0W, 9,0V=3,0A MAX 27,0W;  
15,0V=3,0A MAX 45,0W; 20,0V=2,25A MAX 45,0W

USB type A+A+USB-PD: 5,0V=4,8A MAX 24,0W for total  
and 5,0V=2,4A MAX 12,0W for each

4121/4420  
Made in China

